

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/21/2022
5.1	06/23/2024	10702802-00008	Date of first issue: 06/09/2017

SECTION 1. IDENTIFICATION

Product name : TIRE LEAK SEEKER, Concentrated, 236 mL

Product code : 892.450238

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:

CHEMTREC (24/7): 1-800-424-9300

Urgences liées au transport:

CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Crack detection substance

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Skin irritation : Category 2

GHS label elements

Hazard pictograms :



SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version 5.1 Revision Date: 06/23/2024 SDS Number: 10702802-00008 Date of last issue: 11/21/2022
Date of first issue: 06/09/2017

Signal Word : Warning

Hazard Statements : H315 Causes skin irritation.

Precautionary Statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves.

Response:
P302 + P352 IF ON SKIN: Wash with plenty of water.
P332 + P313 If skin irritation occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Triethanolamine dodecylbenzene sulfonate	Benzenesulfonic acid, dodecyl-, compd. with 2,2',2''-nitrilotris[ethanol] (1:1)	27323-41-7	$\geq 10 - < 30$ *
Alcohols, C10-16, ethoxylated, sulfates, sodium salts	Poly(oxy-1,2-ethanediyl), .alp ha.-sulfo-.omega.-hydroxy-, C10-16-alkyl ethers, sodium salts	68585-34-2	$\geq 1 - < 5$ *
Ethanol	Ethyl alcohol	64-17-5	$\geq 1 - < 5$ *
Methanol	Methyl alcohol	67-56-1	$\geq 1 - < 3$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/21/2022
5.1	06/23/2024	10702802-00008	Date of first issue: 06/09/2017

for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Causes skin irritation.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Not applicable
Will not burn

Unsuitable extinguishing media : Not applicable
Will not burn

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NOx)
Sulfur oxides
Metal oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protection : Use personal protective equipment.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/21/2022
5.1	06/23/2024	10702802-00008	Date of first issue: 06/09/2017

- | | | |
|---|---|---|
| tive equipment and emergency procedures | : | Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8). |
| Environmental precautions | : | Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up | : | Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. |

SECTION 7. HANDLING AND STORAGE

- | | | |
|-----------------------------|---|---|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | Use only with adequate ventilation. |
| Advice on safe handling | : | Do not get on skin or clothing.
Avoid inhalation of vapor or mist.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment. |
| Conditions for safe storage | : | Keep in properly labeled containers.
Store in accordance with the particular national regulations. |
| Materials to avoid | : | Do not store with the following product types:
Strong oxidizing agents |

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version 5.1 Revision Date: 06/23/2024 SDS Number: 10702802-00008 Date of last issue: 11/21/2022
Date of first issue: 06/09/2017

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m ³	CA AB OEL
		STEL	1,000 ppm	CA BC OEL
		STEV	1,000 ppm	CA QC OEL
		STEL	1,000 ppm	ACGIH
Methanol	67-56-1	TWA	200 ppm 262 mg/m ³	CA AB OEL
		STEL	250 ppm 328 mg/m ³	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	250 ppm	CA BC OEL
		STEV	250 ppm 328 mg/m ³	CA QC OEL
		TWAEV	200 ppm 262 mg/m ³	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection
Material : Protective gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/21/2022
5.1	06/23/2024	10702802-00008	Date of first issue: 06/09/2017

workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : pink

Odor : odorless

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : boils before flash

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Will not burn

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/21/2022
5.1	06/23/2024	10702802-00008	Date of first issue: 06/09/2017

Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	No data available
Solubility(ies)		
Water solubility	:	soluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics		
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents.
Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/21/2022
5.1	06/23/2024	10702802-00008	Date of first issue: 06/09/2017

Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method

Components:

Triethanolamine dodecylbenzene sulfonate:

Acute oral toxicity	:	LD50 (Rat): 2,925 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	Assessment: Corrosive to the respiratory tract.
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg Method: OECD Test Guideline 402 Remarks: Based on data from similar materials

Ethanol:

Acute oral toxicity	:	LD50 (Rat): 10,470 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50 (Rat, male): 116.9 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	:	LD50 (Rabbit): > 15,800 mg/kg

Methanol:

Acute oral toxicity	:	Acute toxicity estimate (Humans): 300 mg/kg Method: Expert judgment LD50 (Rat, female): 12.25 ml/kg
Acute inhalation toxicity	:	Acute toxicity estimate: 3 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Expert judgment Remarks: Based on national or regional regulation.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/21/2022
5.1	06/23/2024	10702802-00008	Date of first issue: 06/09/2017

Acute dermal toxicity : Acute toxicity estimate: 300 mg/kg
Method: Expert judgment
Remarks: Based on national or regional regulation.

Skin corrosion/irritation

Causes skin irritation.

Components:

Triethanolamine dodecylbenzene sulfonate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 1 to 4 hours of exposure

Alcohols, C10-16, ethoxylated, sulfates, sodium salts:

Result : Skin irritation

Ethanol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Methanol:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Triethanolamine dodecylbenzene sulfonate:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

Alcohols, C10-16, ethoxylated, sulfates, sodium salts:

Result : Irritation to eyes, reversing within 21 days

Ethanol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

Methanol:

Species : Rabbit
Result : No eye irritation

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/21/2022
5.1	06/23/2024	10702802-00008	Date of first issue: 06/09/2017

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Triethanolamine dodecylbenzene sulfonate:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Ethanol:

Test Type	: Mouse ear swelling test (MEST)
Routes of exposure	: Skin contact
Species	: Mouse
Result	: negative

Methanol:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Triethanolamine dodecylbenzene sulfonate:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: Regulation (EC) No. 440/2008, Annex, B.13/14 (Ames test) Result: negative
-----------------------	---

Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative Remarks: Based on data from similar materials
--

Ethanol:

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/21/2022
5.1	06/23/2024	10702802-00008	Date of first issue: 06/09/2017

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: Ingestion
Result: negative

Methanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: in vitro micronucleus test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Methanol:

Species : Monkey
Application Route : inhalation (vapor)
Exposure time : 7 Months
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Triethanolamine dodecylbenzene sulfonate:

Effects on fertility : Test Type: Three-generation reproduction toxicity study
Species: Rat

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/21/2022
5.1	06/23/2024	10702802-00008	Date of first issue: 06/09/2017

Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Ethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative

Methanol:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Monkey
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test
Species: Monkey
Application Route: inhalation (vapor)
Result: negative

STOT-single exposure

Not classified based on available information.

Components:

Methanol:

Target Organs : optic nerve, Central nervous system
Assessment : Causes damage to organs.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Triethanolamine dodecylbenzene sulfonate:

Species : Rat
NOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/21/2022
5.1	06/23/2024	10702802-00008	Date of first issue: 06/09/2017

Ethanol:

Species	:	Rat
NOAEL	:	1,730 mg/kg
LOAEL	:	3,200 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Triethanolamine dodecylbenzene sulfonate:

Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): 5.7 mg/l Exposure time: 96 h Method: Directive 67/548/EEC, Annex V, C.1.
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 10.6 mg/l Exposure time: 48 h Method: Directive 67/548/EEC, Annex V, C.2.
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): > 56.2 mg/l Exposure time: 72 h Method: Directive 67/548/EEC, Annex V, C.3. EC10 (Desmodesmus subspicatus (green algae)): 17.3 mg/l Exposure time: 72 h Method: Directive 67/548/EEC, Annex V, C.3.
Toxicity to fish (Chronic toxicity)	:	NOEC (Lepomis macrochirus (Bluegill sunfish)): > 0.1 - 1 mg/l Exposure time: 28 d Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 2.8 mg/l Exposure time: 21 d
Toxicity to microorganisms	:	EC10 (Pseudomonas putida): 55 mg/l Exposure time: 18 h

Ethanol:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 14,200 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Ceriodaphnia dubia (water flea)): 5,012 mg/l Exposure time: 48 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/21/2022
5.1	06/23/2024	10702802-00008	Date of first issue: 06/09/2017

Toxicity to algae/aquatic plants : ErC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l
Exposure time: 72 h

EC10 (Chlorella vulgaris (Fresh water algae)): 11.5 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Oryzias latipes (Japanese medaka)): ≥ 79 mg/l
Exposure time: 100 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 9.6 mg/l
Exposure time: 9 d

Toxicity to microorganisms : EC50 (Protozoa): 5,800 mg/l
Exposure time: 4 h

Methanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 15,400 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): $> 10,000$ mg/l
Exposure time: 48 h
Method: DIN 38412

Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): 22,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): $> 1,000$ mg/l
Exposure time: 3 h
Test substance: Neutralized product
Method: OECD Test Guideline 209

Persistence and degradability

Components:

Triethanolamine dodecylbenzene sulfonate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Ethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 84 %
Exposure time: 20 d

Methanol:

Biodegradability : Result: Readily biodegradable.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/21/2022
5.1	06/23/2024	10702802-00008	Date of first issue: 06/09/2017

Biodegradation: 95 %
Exposure time: 20 d

Bioaccumulative potential

Components:

Triethanolamine dodecylbenzene sulfonate:

Partition coefficient: n-octanol/water : log Pow: 1.5
Method: OECD Test Guideline 123

Ethanol:

Partition coefficient: n-octanol/water : log Pow: -0.35

Methanol:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): < 10

Partition coefficient: n-octanol/water : log Pow: -0.77

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1760
Proper shipping name : CORROSIVE LIQUID, N.O.S.
(Triethanolamine dodecylbenzene sulfonate)

Class : 8
Packing group : III
Labels : 8

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/21/2022
5.1	06/23/2024	10702802-00008	Date of first issue: 06/09/2017

Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1760
Proper shipping name : Corrosive liquid, n.o.s.
(Triethanolamine dodecylbenzene sulfonate)
Class : 8
Packing group : III
Labels : Corrosive
Packing instruction (cargo aircraft) : 856
Packing instruction (passenger aircraft) : 852

IMDG-Code

UN number : UN 1760
Proper shipping name : CORROSIVE LIQUID, N.O.S.
(Triethanolamine dodecylbenzene sulfonate)
Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 1760
Proper shipping name : CORROSIVE LIQUID, N.O.S.
(Triethanolamine dodecylbenzene sulfonate)
Class : 8
Packing group : III
Labels : 8
ERG Code : 154
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content : CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: 1.9 %

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/21/2022
5.1	06/23/2024	10702802-00008	Date of first issue: 06/09/2017

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

SAFETY DATA SHEET

according to the Hazardous Products Regulations



TIRE LEAK SEEKER, Concentrated, 236 mL

Version	Revision Date:	SDS Number:	Date of last issue: 11/21/2022
5.1	06/23/2024	10702802-00008	Date of first issue: 06/09/2017

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 06/23/2024
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8